



Technical Data Sheet

AQUAFIN®-CJ3

Art.-No. 2 07203

Bentonite waterstop

Properties:

- Generally approved for use in construction.
- No requirement for imperfect edging.
- Cause of defects will be reduced.
- Self-injecting effect by penetration into cracks and cavities.
- Reswellable.
- Extremely high, form stability, will not become sticky in summer at high temperatures.
- High anorganic contents, therefore, no material fatigue.
- Coated with talcum powder.
- Quick, strong and reliable swelling effect.

Areas of application:

AQUAFIN-CJ3 is a well-developed swellable bentonite waterstop which is economic and reliable. It is used for waterproofing construction joints which are permanently or only temporarily subject to ground or surface water infiltration. AQUAFIN-CJ3 will create a watertight seal in construction joints subjected to water pressure of up to 7 bars.

Application instructions:

AQUAFIN-CJ3 can be fixed with assembly adhesive for swelling tapes or by means of assembly bars or assembly grids.

Technical Data:

Basis:	sodium bentonite, caoutchouc, filler
Form:	the profile is rectangular and flexible
Colour:	black/dark-grey
Size:	18 x 24 mm
Swelling capacity:	> 500%
Weight:	730 g/m
Toxicity:	none
Packaging:	in rolls of 5 m, boxes of 20 m, pallet contents 720 m
Storage:	frostfree, protected against weathering, max. of 5 years in original unopened packs.