


DEKO GROUT+

Multi function grout, ideal for big formats.
Excellent for porcelain, natural or synthetic stone



EN 13888
CG2 WA



- ✚ Nice: smooth, compact surface
- ✚ Durable: easy to clean and resistant to chemical and mechanical stress
- ✚ Healthy: certified EC1 with low emission of volatile organic substances
- ✚ Water repellent, resistant to mold and bacteria
- ✚ Versatile: for internal and external use and for surfaces subject to continuous immersion
- ✚ Quick and easy to apply: long Pot life (45'), but practicable in 6 hours

It is possible to clean immediately after application without waiting.

For joints up to 10 mm width, perfect for rectified tiles.

For floors and walls with heating systems.

Colours matched to the DEKOSIL silicone system.

Benfer®

Via Paletti snc - Castelnuovo Rangone (Mo), 41051 - Italy - tel. +39 059 535 540 - fax +39 059 538 338
P.IVA IT00611061201 - C.F. e Iscr. Reg. Impr. di Modena 03304180379 - R.E.A. MO-385501 - Cap. Soc. €500.000,00 i.v.

info@benfer.it - www.benfer.it





Technical features: DEKOGROUT+ is a special rapid hardening hybrid powder grout made from cement, high tech polymers, aggregates with selected granulometry and special additives; ideal for grouting ceramic floors and walls of every kind, on a great variety of different supports, possessing exceptional waterproofing capabilities and resistance to chemical and mechanical aggression agents. Formulated to harden quickly with no shrinkage, it is suitable for grouting even delicate natural stone products otherwise subject to discoloration or dimensional variations. DEKOGROUT+ is more resistant to stains, mold and bacteria and guarantees a superior appearance, resistance to aging and cleaning of joints. DEKOGROUT+ is available in 13 colors.

Fields of application: can be used for joints in interior and exterior areas, for vitrified mosaics, every type and format of ceramic tiles and natural stone, even that subject to dimensional variations and discoloration. DEKOGROUT+ can be used for joints up to 10 mm in bathrooms, showers, terraces, rooms, balconies and patios, as well as facades, swimming pools, commercial areas, on floating and heated screeds, everywhere you wish to cover with superior beauty, durability, hygiene and cleaning characteristics.

Product Technical Data

Basis:	special cements , mineral aggregates, new generation of additives
Apparent mass volume:	1,20 kg/dm ³
Danger of toxicity:	No. Possible irritation of the eyes and skin upon contact
Inflammable:	No
Mixture ratio:	22-24% of water equivalent to 0,55-0,60 lt of water for 2,5 kg bag
Mixing time:	2-3 minutes (mixer . 300 - 500 r/min)
Consistency of paste:	thixotropic mortar
Mass volume of paste:	1,80 kg/dm ³
Application temperature:	From + 5°C to + 35°C
Foot traffic after:	after 6 hours
Full service:	after 24 hours
Final hardening:	after 7 days
Fulfills the requirements of:	EN 13888CG2WA
Humidity resistance:	excellent
Aging process resistance:	excellent
Temperature resistance:	from -30° C to +90° C
Storage and Duration :	18 months in a dry place, in the original closed package; open bags must be closed again and used as soon as possible, * at 23°C and 50% relative humidity

For more information see the valid technical data sheet and safety sheets of the product and watch the video application on www.benfer.it



Via Paletti snc - Castelnuovo Rangone (Mo), 41051 - Italy - tel. +39 059 535 540 - fax +39 059 538 338
P.IVA IT00611061201 - C.F. e Iscr. Reg. Impr. di Modena 03304180379 - R.E.A. MO-385501 - Cap. Soc. €500.000,00 i.v.

info@benfer.it - www.benfer.it

