

# Declaration of Performance

According Annex III of the Regulation (EU) n°305/2011

For the product

## Benferflex N

### 1054

- |   |  |
|---|--|
| 1. Unique identification code of the product type:  | EN 12004 C2  |
| 2. Identification   | Batch no.: see packaging of the product  |
| 3. Intended use:  | Improved cementitious adhesive for internal and external use   |
| 4. Manufacturer:  | Benfer Schomburg s.r.l.<br>Via Paletti snc<br>41051 Castelnuovo Rangone (MO)   |
| 5. Authorized representative:   | not pertinent  |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as: | System 3<br>Reaction for fire: CWFT  |
| 7. Notified test laboratory:  | The notified testing laboratory: <b>Centro di ricerca e sperimentazione per l'industria ceramica</b> Via Martelli, 26 -40138 Bologna, Italy, identification number: <b>1477</b> performed the determination of the product-type on the basis of type testing under system 3 and issued: test report <b>5217/04</b> |
| 8. European Technical Assessment  | not pertinent  |

**Benfer Schomburg s.r.l.**

41051 Castelnuovo Rangone (MO) - Italy • via Paletti • tel. +39 059 535 540 • fax +39 059 538 338  
P.IVA IT00611061201 • C.C.I.A.A. MO 385501 • Iscr. Trib. MO e C.F. 03304180379 • Cap. Soc. € 500.000 i.v.

[www.benfer.it](http://www.benfer.it) • [info@benfer.it](mailto:info@benfer.it)



9. Declared performance:

Essential characteristic	Performance	Harmonized technical specification
Reaction to fire	E	EN 12004:2007+A1:2012
Bond strength as: Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$	
Durability for: Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$	
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$	
Tensile adhesion strength after freeze/thaw cycles	$\geq 1.0 \text{ N/mm}^2$	
Release of dangerous substances	See MSDS	

10. The performance of the product identified in points 1 and 2 is in conformità with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

**Giorgio Cocchi, president**  
(name and function)

Castelnuovo Rangone, 28-06-2013

This declaration of performance was created electronically. It's valid without manual signature.

The current material safety data sheet and technical data sheet is downloadable under:  
[www.benfer.it](http://www.benfer.it)