

Declaration of Performance

According Annex III of the Regulation (EU) n°305/2011

For the product

Primafuga 5-15

1. Unique identification code of the product type:

EN 13888 CG2 WA

2. Identification

Batch no.: see packaging of the product

3. Intended use:

Improved cementitious grout with additional characteristic of high reduced water absorption

and high abrasion resistance

4. Manufacturer:

Benfer Schomburg s.r.l.

Via Paletti snc

41051 Castelnuovo Rangone (MO)

5. Authorized representative:

not pertinent

6. System or systems of assessment and

verification of constancy of performance of the construction

product as:

not pertinent

7. Notified test laboratory: not pertinent

8. European Technical Assessment

not pertinent





9. Declared performance:

Essential characteristic	Performance	Harmonized technical specification
Abrasion Resistance	≤ 1000 mm³	
Flexural strength after dry storage	≥ 2.5 N/mm ²	
Flexural strength after freeze-thaw cycles	≥ 2.5 N/mm ²	
Compressive strength after dry storage	≥ 15 N/mm²	
Compressive strength after freeze-thaw cycles	≥ 15 N/mm²	
Shrinkage	≤ 3 mm/m	EN 13888:2009
Water absorption after 30 min	≤ 2 g	
Water absorption after 240 min	≤ 5 g	

10. The performance of the product identified in points 1 and 2 is conform to the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and oh behalf of the manufacturer by:

Giorgio Cocchi, president

(name and function)

Castelnuovo Rangone, 25-07-2013

This declaration of performance was created electronically. It's valid without manual signature.

The current material safety data sheet and technical data sheet is downloadable under: www.benfer.it

