

Declaration of Performance

According Annex III of the Regulation (EU) n°305/2011

For the product

MARMOFLEX-HT

1087

- | | |
|---|--|
| 1. Unique identification code of the product type: | EN 12004 C2 F |
| 2. Identification | Batch no.: see packaging of the product |
| 3. Intended use: | Improved, fast setting, cementitious adhesive for ceramic tile. Internal and external use |
| 4. Manufacturer: | Benfer Schomburg s.r.l.
Via Paletti snc
41051 Castelnuovo Rangone (MO) |
| 5. Authorized representative: | not pertinent |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as: | System 3
Reaction for fire: CWFT |
| 7. Notified test laboratory: | The notified testing laboratory: Modena Centro Prove srl Via Sallustio 78, Modena, Italy , identification number: 1599 performed the determination of the product-type on the basis of type testing under system 3 and issued: test report 20144807 |
| 8. European Technical Assessment | not pertinent |

Benfer Schomburg s.r.l.

41051 Castelnuovo Rangone (MO) - Italy • via Paletti • tel. +39 059 535 540 • fax +39 059 538 338
P.IVA IT00611061201 • C.C.I.A.A. MO 385501 • Iscr. Trib. MO e C.F. 03304180379 • Cap. Soc. € 500.000 i.v.

www.benfer.it • info@benfer.it



9. Declared performance:

Essential characteristic	Performance	Harmonized technical specification
Reaction to fire	E	EN 12004:2017
Bond strength as: Early tensile adhesion strength Initial tensile adhesion strength	≥ 0.5 N/mm ² ≥ 1.0 N/mm ²	
Durability for: Tensile adhesion strength after water immersion Tensile adhesion strength after heat ageing Tensile adhesion strength after freeze/thaw cycles	≥ 1.0 N/mm ² ≥ 1.0 N/mm ² ≥ 1.0 N/mm ²	
Release of dangerous substances	See MSDS	

10. The performance of the product identified in points 1 and 2 is conform to the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:


Giorgio Cocchi, president
(name and function)

Castelnuovo Rangone, 28-06-2013

This declaration of performance was created electronically. It's valid without manual signature.

The current material safety data sheet and technical data sheet is downloadable under:

www.benfer.it

 1599	Benfer Schomburg s.r.l. Via Paletti, sn 41051 Castelnuovo Rangone (Mo) Italy
<p style="text-align: center;"> 17 DoP n°1087 EN 12004:2017 MARMOFLEX-HT Fast setting, improved cementitious adhesive for internal and external tiling </p>	
Reaction to fire	Class E
Release of dangerous substances	see MSDS
Bond Strength, as:	
- Early tensile adhesion strength	$\geq 0.5 \text{ N/mm}^2$
- Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
Durability, for:	
- Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
- Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
- Tensile adhesion strength after freeze/thaw cycles	$\geq 1.0 \text{ N/mm}^2$